

Corporate and Education Solutions

UTV SC



UNILUMIN GROUP CO., LTD.

Headquarters

1-3 floor, Building B, 18 Haoye Street,
Fuhai Sub-district, Baoan District, Shenzhen, China

Pingshan Science & Technology Park

6 Lanjing North Road, Pingshan District,
Shenzhen 518118 China

Daya Bay Factory

Longsheng Fifth Road, Western Daya Bay,
Huiyang District, Huizhou 516211 China



Tel: +86-755-29918999

Fax: +86-755-29912092

E-mail: sales@unilumin.com

Website: www.unilumin.com

Published July 2024

www.unilumin.com

HQ-MKT-HC-009

Why All In One

Now

Before



- Click and Share
- Support wireless screen casting of multiple devices simultaneously:
Computers/ | Mobile phones/ | Tablets/

- Wired Connection
- Not easy to share content
- Table is covered with cords



High Integration Design

Complex Combination of Devices

Capture their attention in record time

Transform your business environment to capture the attention of visitors and employees with intelligent meeting practices and presentations. Unilumin digital displays and Unilumin's All-in-one can improve overall corporate communication.

Now

Before



Effective collaboration

Enable effective collaboration with integrated design and 5 gigabyte ultra-large signal transmission.

Engaging communication

Update your corporate workplace with excellent visual experience to attract more attention for all. What's more, the use intelligent functions improve the boundaries of communication exponentially.

Easy management

Security and remote management are top priorities for corporations. Equip your conference room with displays and make your meeting more secure with ease.

Enterprise Solution

Unilumin enterprise solutions provide high-integrated communication windows with superior digital displays. With high-quality, excellent visual performance, and easy-to-use features to enhance the work environment, it will improve work performance and save on overall business costs.



Training Room



Meeting Room



Report Hall

Education Solution

Unilumin education solutions provide a comfortable viewing experience, user-friendly design to change learning styles and environment with interactive displays. Unilumin UTV is designed for schools and training institutions to achieve new and improved teaching practices. Utilizing LED solutions can make distance teaching a reality and empower classrooms and manage education data to reach higher teaching quality.



Classroom



Lecture Hall

For your highly efficient meeting experience with long-time eye-comfortable viewing



UTV SC All-in-one

- Full flip chip COB
- Common cathode
- EBL+ technology

Cinema-Grade Quality

Smooth handling

- Remote control
- 3-in-1 on/off key
- Support four screen projection
- Multiple types of interfaces

Smooth Optical Technology

Reduce eye fatigue during viewing

Real pixel dot to dot HD display effect

TüV anti-blue light

Built-in audio system

60% energy saving compared with conventional displays

Multi-protection

5G 5 gigabit (Faster and more stable than standard 1.2 Gigabit transfers)

4K ULTRA HD EXPERIENCE EMBRACE HIGH QUALITY VISUALS

Advanced multi-layer nanoscale processing on the pixel surface delivers exquisite, micro-level dot-to-dot high definition imagery, boasting high contrast and minimal reflectivity for an unparalleled viewing experience.



ALL-IN-ONE HIGH INTEGRATION DESIGN

Standard Android system, built-in full-range professional audio, self-amplifier design, plug and play supported, convenient and efficient installation.



Android

Standard operating system



Internal speaker

Built-in full frequency double bass professional speaker



Self-amplifier design

intelligent, easy to use



Easy installation

Efficient and convenient

ENJOY PEACE OF MIND WITH OUR MODULE LEVEL PROTECTION

Anti-collision

Dustproof

Damp-proof

09:30

2023/06/22 Thursday

HDMI IN

Wireless IN

Document

More

09

A large green percentage '60%' is displayed at the top of the slide. Below it, a monitor displays a green-themed advertisement with the text 'Your Life, Our Mission' and 'GO GREEN, WE ARE SERIOUS'. The monitor is positioned over a background of lush green foliage and a waterfall.

60% ENERGY SAVING COMPARED WITH
CONVENTIONAL DISPLAYS

60%

Your Life, Our Mission

GO GREEN,
WE ARE SERIOUS

中国环境标志
CHINA ENVIRONMENTAL LABEL
绿色产品标志

Begin With R&D GO For Production End In Use

10

A large green percentage '60%' is displayed in the upper half of the slide. Below it, a monitor displays a green-themed advertisement with the text 'Your Life, Our Mission' and 'GO GREEN, WE ARE SERIOUS'. The monitor is positioned over a background of lush green foliage and a waterfall.

TÜV CERTIFIED ANTI-BLUE LIGHT, BETTER VISUAL EXPERIENCE

Change the blue spectrum distribution from the source and revolutionize your visual experience. Our cutting-edge blue light barrier cares for your eye health without compromising the integrity of the color gamut, ensuring vibrant picture quality and eliminating any unwanted yellowing.



Parameter	Value		
Model	UTV SC108	UTV SC135	UTV SC162U
Size (inch)	108	135	162
Display Ratio	16:9	16:9	16:9
Resolution (W*H)	1920 (H) x 1080 (V)	1920 (H) x 1080 (V)	3840 (H) x 2160 (V)
Pixel Pitch (mm)	1.25	1.5625	0.9375
Visible Area (㎡)	3.24	5.0625	7.29
Dimensions (mm)	2411 x 1476 x 30.4	3011 x 1813.5 x 30.4	3611 x 2151 x 30.4
Weight (kg)	80	126	180
Material	Die-Cast Aluminum	Die-Cast Aluminum	Die-Cast Aluminum
Maintenance	Front	Front	Front
LED Type	COB	COB	COB
Horizontal/Vertical Viewing Angle (degree)	H:170°/V:160°	H:170°/V:160°	H:170°/V:160°
Brightness (cd/㎡)	600 (adjustable)	600 (adjustable)	600 (adjustable)
Refresh Rate (Hz)	3840	3840	3840
Video Frame Rate (Hz)	50/60	50/60	50/60
Contrast Ratio	10000:1	10000:1	10000:1
Color Temperature (K)	2000~9500	2000~9500	2000~9500
Operating System	Dual system (Android & Windows)	Dual system (Android & Windows)	Dual system (Android & Windows)
Function	Touch Available	Touch Available	/
Rated Power (Speaker)	12Wx2(Built-in)	12Wx2(Built-in)	12Wx2(Built-in)
Input Voltage	AC 100 V ~ 240 V	AC 100 V ~ 240 V	AC 100 V ~ 240 V
Peak Power Consumption (W)	1005	1435	2400
Operating Temperature/Humidity	-10°C ~ +45°C/10~80% RH frost-free	-10°C ~ +45°C/10~80% RH frost-free	-10°C ~ +45°C/10~80% RH frost-free
Storage Temperature/Humidity	-20°C ~ +50°C/10~70% RH frost-free	-20°C ~ +50°C/10~70% RH frost-free	-20°C ~ +50°C/10~70% RH frost-free